



- Standard - Extension -

Specification Sheet

SPECIFICATION	FOLDSCAF STANDARD	FOLDSCAF EXTENSION PACK
<i>Erected</i>		
Length	1.9m	1.9m
Width	0.76m (outside to outside)	0.76m
Height	2.0m	3.0m
Working platform height	0.4m,0.7m,1.0m	1.3m,1.6m,1.9m
Platform weight	12kg	12kg
Platform load rating	225kg	225kg
Platform dimensions	1.9m X 0.58m	1.9m X 0.58kg
Scaffold weight	11kg	11kg
Wheel sizes	12cm (5 in) or 20cm (8 in)	12cm (5 in) or 20cm (8 in)
5 inch Wheel weights	2.5kg each	2.5kg each
8 inch Wheel weights	9.0kg each	9.0kg each
Rungs	6	8
Distance between rungs	300mm (centre to centre)	300mm (centre to centre) 500mm (mid rail to guardrail)
Platform material	Aluminium T6 6061, plywood (non slip)	Aluminium T6 6061, plywood (non slip)
Scaffold material	Aluminium T6 6061	Aluminium T6 6061
Wall thickness	2.0mm	2.0mm
Tube diametre	50.8mm	50.8mm
Finish	Smooth / Ridged	Smooth / Ridged
<i>Dismantled</i>		
Length	1.0m	1.0m
Width	2.0m	2.0m
Height	0.3m	0.5m

