



Ph: 1300 MR SCAFFOLD

(Ph:1300 677 223)

www.mrscaffold.com.au

SAFE WORKING LOAD GUIDE MULTIPLE WORKING PLATFORMS

Applies to: **EASYSCAF** **SUPASCAF** **LOCKSCAF**

Frame Width	Plant Design Rego. Work Cover NSW	Mr. Scaffold Brand	Max. Working Platform Height	Max. Load per Level	Max. live Load per Bay	Tower Rated for Duty
Single (0.7m)	PFS 6-130207/10	SUPASCAF LOCKSCAF	6.0m	450kg	680 kg	Medium
			8.1m	450kg	640 kg	Medium
Double (1.3m)	PFS 6-130209/10	SUPASCAF LOCKSCAF	6.0m	450kg	760 kg	Medium
			8.0m	450kg	695 kg	Medium
			9.6m	450kg	620 kg	Medium
Triple (1.8m)	PFS 6-130206/10	SUPASCAF LOCKSCAF	6.0m	450kg	660kg	Medium
			8.0m	450kg	510kg	Medium
			10m	450kg	420kg	Medium
			12m	225kg	345kg	Light
Quad (2.5m)	PFS 6-130208/10	SUPASCAF LOCKSCAF	6.0m	450kg	565 kg	Medium
			8.0m	225kg	385 kg	Light
			10.0m	225kg	255 kg	Light
			12.0m	225kg	225 kg	Light
Single (0.7m)	PFS 6-97368/07	EASYSCAF	6.0m	225kg	225kg	Light
Double (1.3m)	PFS 6-97368/07	EASYSCAF	6.0m	225kg	225kg	Light
Medium Duty = 450kg						
Light Duty = 225kg						
* Please read Safe Erection Procedure, Hazard Reduction and Safety Compliance BEFORE USE.						
* YOU MAY BE REQUIRED TO CARRY OUT YOU OWN SWMS / JSA BEFORE USE.						
* Access Platforms every 2m are allowed for.						
* Access Platforms are not included as working platforms and for access only.						

© Copyright 2006 - Mr Scaffold Pty Ltd

Other leading brands from Mr Scaffold

FOLDSCAF

EASYSCAF

SUPASCAF

LOCKSCAF

KWIKSCAF